

IN THE CLAIMS:

1. (Original) A high-pressure discharge lamp comprising:

a bulb that includes a light emitting part having an electrode pair disposed and a discharge space formed therein, and a first sealing part and a second sealing part provided at different ends of the light emitting part; and

- 5 a proximity conductor formed from a lead wire, a section of the lead wire being wound around an outer circumference of at least one of the first sealing part and a section of the light emitting part to form a wound portion, and a remaining section of the lead wire forming a lead portion that extends from the wound portion across the light emitting part in proximity to or contacting with an outer surface of the light emitting part, to a side of the discharge lamp on which the second sealing part is disposed, wherein

the lead portion is electrically connected to the electrode, of the pair, positioned nearer the second sealing part, and

- at least a section of the wound portion is wound substantially spirally at least 0.5 turns in a range from a 2nd reference plane to a 3rd reference plane, and a closed loop around one of the light emitting part and the first sealing part does not exist within the range, where the 2nd to 3rd reference planes are parallel to a 1st reference plane lying orthogonal to a bulb longitudinal direction and including an end of the discharge space positioned at a base portion of the electrode nearer the first sealing part, the 2nd reference plane being distant 5 mm from the 1st reference plane along the first sealing part and the 3rd reference plane passing through a tip of the electrode
- 20 nearer the second sealing part.

2. (Cancelled)

3. (Original) The high-pressure discharge lamp of claim 1, wherein a shortest distance from the lead portion to the inner surface of the light emitting part is 10 mm or less in a range defined by the 1st reference plane and a 4th reference plane parallel to the 1st reference plane and including an end of the discharge space positioned at a base portion of the electrode nearer
5 the second sealing part.

4. (Original) The high-pressure discharge lamp of claim 1, wherein in a range defined by the 2nd and 3rd reference planes, a pitch interval of the substantially spirally wound portion of the proximity conductor is at least 1.5 mm.

5. (Currently Amended) A lighting method for a high-pressure discharge lamp as in claim 1, ~~according to which a discharge of the high-pressure discharge lamp is initiated after~~
~~applying a high-frequency voltage is applied to the electrode pair prior to application of a high-~~
voltage pulse to initiate a discharge of the high-pressure discharge lamp.

6. (Original) The lighting method lamp of claim 5, wherein a frequency of the high-frequency voltage is in a range of 1 kHz to 1 MHz.

7. (Original) The lighting method lamp of claim 5, wherein an amplitude of the high frequency voltage is at least 400 V.

8. (Currently Amended) A lighting device for lighting a high-pressure discharge lamp as in claim 1, comprising a voltage applying unit operable to apply a high-frequency voltage to the electrode pair prior to application of a high-voltage pulse to initiate a discharge of the high-pressure discharge lamp.

9. (Original) The lighting method lamp of claim 8, wherein a frequency of the high-frequency voltage is in a range of 1 kHz to 1 MHz.

10. (Original) The lighting method lamp of claim 8, wherein an amplitude of the high-frequency voltage is at least 400 V.

11. (Original) A high-pressure discharge lamp device comprising a high-pressure discharge lamp as in claim 1 and a lighting device as in claim 8 for lighting the high-pressure discharge lamp.

12. (Original) A lamp unit in which a high-pressure discharge lamp as in claim 1 is incorporated within a concave reflective mirror.

13. (Original) An image display device using a high-pressure discharge lamp device as in claim 11.

14. (Original) A headlight device using a high-pressure discharge lamp device as in claim 11.